

# SAFETY DATA SHEET (EC 1907/2006)

Hanwha L&C Corporation

Hanex Acrylic Joint Adhesive

Revision date

Dec.24.2012

Page

1 / 6

**Hanex<sup>®</sup>**  
Solid Surfaces

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product information

Trade name : Hanex Acrylic Joint Adhesive (Component A)  
Supplier : HANWHA L&C CORPORATION, HANEX SALES  
#1, JANGGYO-DONG, JUNG-GU, SEOUL, 100-797,

Use of the Substance / : For industrial use

Preparation

Function : Adhering to solid surface

## 2. HAZARDS IDENTIFICATION

### Main Hazards

Harmful if swallowed.

Risks of serious damage to eyes.

### Health Effects-Eyes

Liquid or mist will cause severe conjunctiva irritation and corneal damage.

### Health Effects-Skin

Material may cause irritation.

Repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis.

### Health Effects-Ingestion

Swallowing may have the irritation of mouth, throat and digestive tract, nausea, difficulty with breathing, lung damage.

### Health Effects-Inhalation

Low volatility makes acute effects unlikely at ambient temperatures.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Information on ingredients / Hazardous components

Chemical nature of the preparation: benzyl peroxide, plasticizer

#### Hazardous components:

Benzyl peroxide:  $\geq 3.0$  weight(%) \*Tube Type: 5.0 weight (%), Cartridge Type: 3.1 weight (%)

XI: 36-43

CAS-No: 94-36-0

EC-No: 202-327-6

Butyl benzyl phthalate:  $\geq 60$ weight(%) \*Tube Type: 95.0weight(%), Cartridge Type: 60weight(%)

CAS-No: 84-74-2

EC-No: 201-557-4

# SAFETY DATA SHEET (EC 1907/2006)

Hanwha L&C Corporation

Hanex Acrylic Joint Adhesive

Revision date

Dec.24.2012

Page

2 / 6

**Hanex<sup>®</sup>**  
Solid Surfaces

## 4. FIRST AID MEASURES

### General advice

Remove contaminated or saturated clothing.

### Inhalation

Move to fresh air. Oxygen or artificial respiration if needed. Consult physician after significant exposure.

### Skin contact

Wash off immediately with soap and plenty of water.

### Eye contact

Rinse thoroughly with plenty of water at least 18 minutes and consult a Physician.

Keep eye wide open while rinsing.

### Ingestion

Never give anything by mouth to unconscious person. Rinse mouth.

Ingest activated charcoal. Call a physician immediately.

### Notes to physician

If required, therapy of irritative effect.

If substance has been swallowed:

Early endoscopy in order to assess mucosa lesions in the oesophagus and stomach which may appear.

If necessary, aspirate leftover substance.

## 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Use dry chemical, CO<sub>2</sub>, Water spray or "alcohol" foam.

### Extinguishing media which must not be used for safety reasons

High volume water jet

### Special Hazards

This product may give rise to hazardous fumes in a fire.

### Protective Equipment

Wear self contained breathing apparatus.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions

Ensure adequate ventilation. Use personal protective equipment.

Remove all sources of ignition.

### Environmental precautions

Do not let product enter drains.

### Methods for cleaning up

Soak up with inert absorbent material. Clean with detergents.

Avoid solvents.

**7. HANDLING AND STORAGE****Handling****Technical measures/Precautions**

Keep product and empty container away from heat and sources of ignition.

**Safe handling advice**

Do not smoke.

**Storage****Technical measures/Storage conditions**

Keep at temperatures below 30°C.

Water mist may be used to cool closed containers.

Incompatible products: Reacts violently in contact with acids, amines, driers.

Polymerization accelerators and easily oxidized materials.

**Packing material**

Not applicable

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Personal protective equipment****Respiratory protection**

Repeated and prolonged exposure to solvents may cause brain and nervous system damage.

It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

**Hand protection**

Solvent-resistant gloves

**Eye protection**

Safety glasses

**Hygiene measures**

Keep away from food, drink and animal feeding stuffs. Wash hands before Breaks and at the end of workday.

**Exposure controls****National occupational exposure limits**■ **Benzoyl peroxide:**

TLV-TWA=5 mg/m<sup>3</sup>/A4/ACGIH(1997)

Butyl benzyl phthalate: TLV-TWA=5 mg/m<sup>3</sup>/A4/ACGIH(1997)

# SAFETY DATA SHEET (EC 1907/2006)

Hanwha L&C Corporation

Hanex Acrylic Joint Adhesive

Hanex<sup>®</sup>  
Solid Surfaces

Revision date

Dec.24.2012

Page

4 / 6

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

Form:	liquid
Color:	light yellow
Odour:	slight
PH: (°C) (at g/l H <sub>2</sub> O)	not applicable
Decomposition temperature	103 °C
Flash point:	above 100 °C          closed up
Autoignition temperature	no data available °C
Vapour pressure: ( 147 °C)	1.3hps
Relative density: (°C)	from 1.03kg/l to 1.07kg/l
Solubility:	
Water Solubility (°C)	Immiscible g/l
Viscosity :(°C)	no data available mpa.s
Explosion limits:	-lower no data available vol. % -upper no data available vol. %

## 10. STABILITY AND REACTIVITY

### Conditions to avoid

**Decomposition starting from 103 °C:** Benzyl peroxide 100%

### Materials to avoid:

Reacts violently in contact with acids, amines, driers, polymerization  
Accelerators and easily oxidized materials.

### Hazardous decomposition products:

Benzoic acid, biphenyls, benzene

## 11. TOXICOLOGICAL INFORMATION

Repeated and prolonged exposure to solvents may cause brain and nervous system damage.

### Acute toxicity

#### Benzoyl Peroxide:

LD50/oral/rac = 7710 mg/kg, RTECS, 19455

Butyl benzyl phthalate: LD50/oral/rac = 8000 mg/kg, RTECS, 59814

Local effects not applicable

**SAFETY DATA SHEET (EC 1907/2006)****Hanwha L&C Corporation****Hanex Acrylic Joint Adhesive**

Revision date

Dec.24.2012

Page

5 / 6

**Hanex<sup>®</sup>**  
Solid Surfaces**12. ECOLOGICAL INFORMATION****Mobility**

The product will not dissolve in water.

**Persistence/Degradability**

The product is expected to be partially or slowly biodegradable.

**Bio-accumulation**

The product is not expected to bioaccumulate.

**Ecotoxicity**

No data

**13. DISPOSAL CONSIDERATIONS****Waste from residues / unused products**

Do not allow material to contaminate ground water system.

Prevent product from entering drains.

**Contaminated packaging**

Can be incinerated, when in compliance with local regulations.

**14. TRANSPORT INFORMATION****UN-NO: 3269****ADR/RID**

Class: 3

Item: 5(C)

ADR/RID=Labels: 3

TREM-CARD: 30G80

HI/UN NO:

Proper shipping name: Adhesives

**ICAO**

UN/ID NO: 1133

Class: 3

Sub risks:

Packing group: III

ICAO-Labels: Flammable liquid

Proper shipping name: Adhesives

**IMO**

Class: 3.2

IMDG Page: 3174

Sub risks:

Packing group: III

IMO-Labels: Flammable liquid

Pms: 3 -05

MPAG: 330

Proper shipping name: Adhesives

# SAFETY DATA SHEET (EC 1907/2006)

Hanwha L&C Corporation

Hanex Acrylic Joint Adhesive

Revision date

Dec.24.2012

Page

6 / 6

**Hanex**  
Solid Surfaces

## 15. REGULATORY INFORMATION

The product is classified and labeled in accordance with EC-Directive 88/379

Symbol(s):	Xi -irritant,
Contents:	Benzoyl peroxide
R-phrase:	R43-May cause sensitization by skin contact
S-phrase:	S14-Keep away from easily oxidizable materials S16-Keep away from source of ignition – No smoking S24/25-Avoid contact with skin and eyes S37-Wear suitable gloves

## 16. OTHER INFORMATION

When used in a mixture, read the labels and safety data sheet of all components,

END USE: adhesives.

Do not use in medical applications involving permanent implantation in the human body.

The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.